

D-FOAMER

ANTIFOAM AGENT



An antifoam concentrate designed primarily to defoam unwanted or excess produced AFFF fire fighting foam.

Quickly eliminates foam so reducing the risk of foam / hydrocarbon carry over to industrial separators.

FEATURES

An effective, easily diluted defoaming agent suitable for use in all types of defoaming applications, including:

- Fire fighting foams
- Amine scrubbing
- Traffic film removers
- Rigwash and degreasers
- Cutting oils
- Sewage and effluent processes

HOW TO USE

- Dilute in water at 0.6 - 3.0L of D-Foamer to 1000L of water, depending upon drainage time of foam.
- Spray over foam surface and leave to defoam.

PHYSICAL PROPERTIES

Appearance	Off-white viscous emulsion
Specific gravity @ 25°C	1.0
Percentage silicone	30
pH at 20°C	~7
Viscosity @ 20°C mPas	Non-viscous
Freezing point (°C)	TBC
Boiling point (°C)	>35
Lowest use temp. (°C)	2
Max. storage temp. (°C)	35
Min. storage temp. (°C)	0

METHOD OF USE

D-Foamer disperses easily in both hot and cold aqueous systems, requiring only mild agitation to disperse it completely in the foaming system. The quantity of antifoam required can only be found by experiment. In general, between 0.06% and 0.3% of the product is all that is required, ie 0.6 - 3 litres of product per 1000 litres of foaming media.

ENVIRONMENTAL IMPACT

- Very low order of toxicity
- Not classified as hazardous to the environment

APPLICATIONS

D-Foamer is an effective, stable antifoam in all types of applications including Fire fighting foams, Adhesives, Amine scrubbing, Cutting oils, Traffic Film Removers, Rig wash and Sewage/ Effluent processes.

STORAGE AND SHELF LIFE

Keep in the original, unopened manufacturer's supplied container and store between 2°C and 35°C. Do not allow to freeze. Shelf life of unopened containers is 12 months from date of manufacture. For use after this time, please contact us.

DISPOSAL

Excess product to be disposed of by a specialised disposal company.

TECHNICAL SERVICES AND SALES SUPPORT

For our UK customers, Aberdeen Foam is available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515

PACK SIZES

Available in the following sizes:
5 Litre, 20 litre, 25 litre containers

Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.



Supplied by
Oil Technics (Fire Fighting Products) Ltd
Linton Business Park, Gourdon,
Aberdeenshire, Scotland UK DD10 0NH

T: +44 (0) 1561 361515 F: +44 (0) 1561 361001
E: info@firefightingfoam.com W: www.firefightingfoam.com



JOIFF



Fire Sector Federation