

ABERDEEN FOAM FOAM SEAL OIL



Sealing barrier helps to minimise evaporation & deterioration of foam concentrates



Foam Seal Oil is designed for use as a sealing barrier on stored Foam Concentrate to minimise evaporation & deterioration.

Foam Seal Oil is non-reactive and remains on the surface of the foam concentrate while stored in your tanks.

HOW TO USE

- Add to the surface of your foam concentrate immediately after it is placed in its storage tank.
- A depth of approximately 6mm is recommended.
- Not recommended for apparatus tanks or tanks subject to excessive vibration.

PHYSICAL PROPERTIES

Appearance	Colourless oil
Specific gravity @ 20°C	0.88
pH @ 20°C	~7
Viscosity @ 20°C mPas	Viscous
Min. use temp. (°C)	2
Max. use temp. (°C)	49

ENVIRONMENTAL IMPACT

- Biodegradable
- Negligible ecotoxicity
- Not classified as hazardous to the environment

APPLICATIONS

Foam Seal Oil is designed for use as a barrier between the stored foam concentrate and the air in order to reduce evaporation and deterioration.
NOT FOR USE IN FIRE FIGHTING APPLICATIONS.

STORAGE AND SHELF LIFE

Best stored as supplied in original, unopened containers or in suitable tanks. Use and store in well ventilated areas.

To prolong the shelf life, do not expose to temperature extremes and prevent contamination from foreign materials.

DISPOSAL

Excess product to be disposed of by a specialised disposal company.

TECHNICAL SERVICES AND SALES SUPPORT

For our UK customers, Aberdeen Foam is available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515

PACK SIZES

Available in 25 litre containers.

Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.



Oil Technics (Fire Fighting Products) Ltd

Linton Business Park, Gourdon,
Aberdeenshire, Scotland UK DD10 0NH

T: +44 (0) 1561 361515

F: +44 (0) 1561 361001

E: info@firefightingfoam.com W: www.firefightingfoam.com

